FLEXSHADE | TENSION ZIP

OPTIONS

RETRACTABLE PATIO AWNINGS Order Form



	Company:	Date: P.O. #:		
	Address:	City: State:		
	Telephone: Fax or Email:	Contact:		
SY	STEM SPECIFICATIONS	FILL IN, CHECK OR CIRCLE	PRICE	
FR	AME OPTIONS (Measure to the nearest ½"; Note: we do not take any deductions.)			
Fin	ished System Width – Maximum 196" (1) Mounting bracket centerline is 2 ½" narrower	Width – Maximum 196" ① Mounting bracket centerline is 2 ½" narrower than the finished width! Inches Length – Maximum 240" Inches		
Fin	ished System Length – Maximum 240"			
Frame Color (select one)		☐ White ☐ Sand ☐ Black ☐ Ivory ☐ Bronze ☐ Smooth Silver		
Headbox Type (select one)		☐ Angled ☐ Curved		
Lef	de Channel Mounting Brackets (see diagram below)		djustable	
Rig	ht Side Channel Mounting Brackets (see diagram below)	Mounting Brackets (see diagram below) □ L-Angled □ Single Adjustable □ Dual Adjustable		
FABRIC SELECTION (Additional fabric options may be available upon request.)				
Fabric Type				
Fabric Color Name & Number SHEERWEAVE: Pearl Gray—V20 Charcoal—V21 Charcoal/Gray—V22 Charcoal/Chestnut—V24 Charcoal/Alpaca—V32 STARSCREEN: Black—T8024/400 Silver—T8079/400 White—T8015/400 Smoked Pearl—T8971/497		Name: Number:		
EL	LECTRONICS AND CONTROLS (System includes a 24 ft. motor cord without plug, and Hand Held Waterproof Remote Control.)			
Мо	tor Location – facing front (see diagram below)	ngram below)		
Motor Cord Exit		□ Back □ Side □ None		
Motor Cord Length (24 ft. standard)		□ 6 ft. □ 10 ft. □ 24 ft.		
	NEMA 15Amp Straight Blade Plug NEC approved in use outlet cover required.	☐ Yes ☐ No		

Comments:

Additional Single Channel Waterproof Remote (one included)

Save this completed form and email it to: orders@summerspace.com

Five Channel Waterproof Remote Solar Powered Rain Sensor

> Save this completed form and email it to: orders@summerspace.com

Additional: ☐ Yes ☐ No

☐ Yes ☐ No

☐ Yes ☐ No

Freight charges are prepaid and added at carrier rates.

Exchange: ☐ Yes ☐ No

TOTAL





